





ECOGEM S9041HO/TC - 13W

High output dimmable IP44 LED downlight with selectable colour temperature

Application

Ideal for any residential or commercial interior space

Design Specifications

- Easy selectable colour temperature with an inbuilt DIP switch, 3000K/4200K/5700K
- Durable die-cast aluminium body profile
- Stylish white powder coat finish or satin nickel
- Colour trim options: (black ring S9041 BK RING), (satin nickel S9041 SN RING), (silver ring S9041 SL RING)
- Remote constant current trailing edge dimmable LED driver, with flex and plug
- High efficiency SMD LED chips and quality opal polycarbonate diffuser.





















Performance

Dimmable - YES

Dimmer Type - Trailing edge, optional 1-10V, DALI / DSI

Technical Specification

\$9041HO/TC/WH 240 13 1040/1200/1100 3000/4200/5700 90 YES	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	ССТ (К)	Beam Angle (°)	Dimmable
	S9041HO/TC/WH	240	13	1040/1200/1100	3000/4200/5700	90	YES

Model No.	CRI	Body Colour	Cut Out (mm)	Diameter (mm)	Dim (mm)
S9041HO/TC/WH	80	WHITE	92	103	40(H)

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".





Dimensions



Dimensions





THE SFI SYSTEM ELIMINATES LED FLICKERING.

SIMPLY MATCH THE ECOGEM SFI DOWNLIGHT WITH THIS SDD400SFI DIMMER







DIM with FLICKER CONTROL

For related products please scan me



NSW/ACT: 02 9723 3099 QLD: 07 3879 5999 VIC/TAS/SA/NT: 03 9532 3168 WA: 08 9248 7458

