PREMIER S9075TC DP - 23/30W

IP64 30W LED downlight with selectable colour temperature and power

Application

Ideal for any commercial interior space requiring flexibility in power selections

Design Specifications

- Premium aluminium body profile, CA90 rated
- Stylish white powder coat finish
- Quality opal polycarbonate diffuser
- High efficiency SMD LED chips
- Remote constant current non-dimmable LED driver, with flex and plug

IP64 · ta40 · DUAL POWER · WW TC DL CW · 3 YEARS COMMERCIAL WARRANTY · VEET APPROVED

Technical Specification

Model No.	Input Voltage (V/AC)	Multiple Wattage	Lumens (lm)	CCT (K)	Beam Angle (°)	Dimmable
S9075TC/WH/DP	240	23/30	2600/3100/2800	3000/4000/5700	90	OPTIONAL

| Model No.	CRI	Body Colour	Cut Out (mm)	Diameter (mm)	Dim (mm)	VEET
S9075TC/WH/DP	80	WHITE	195	230	75(H)	YES

Note: Lumens (lm) shown are at FULL power

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions

Dimensions

Ø 195 mm
H 75 mm
Ø 230 mm

NSW/ACT: 02 9723 3099
QLD: 07 3879 5999
VIC/TAS/SA/NT: 03 9532 3168
WA: 08 9248 7458
www.sal.net.au

- 1 -

PDF Prepared: 11.4.2022 7:45pm
Last page update: Sep 2021
© Copyright SAL - All Rights Reserved

Photometric Data

Photometric Data

Unit: cd   C0/C180 _____   C90/C270 _____

S9075TC/WH/DP at 4000K

THE SFI SYSTEM ELIMINATES LED FLICKERING.

SIMPLY MATCH THE ECOGEM SFI DOWNLIGHT WITH THIS SDD400SFI DIMMER.

DIMMABLE

DIM with FLICKER CONTROL

For related products please scan me

100% AUSTRALIAN OWNED AND OPERATED